



Serial No.: 09/818,554
Docket No.: 1081.1112

SERVICE PROVISION METHOD VIA A NETWORK AND SERVICE PROVISION SYSTEM USING THE SAME

Field of the Invention

[0001] The present invention relates generally to a service provision method via a network such as the Internet, more particularly, to a service provision method and a service provision system ~~using the same by which a stable service can be~~ provided; ~~when more access requests to a server providing the service become concentrated to one server, which provides the service.~~

Description of the Related Art

[0002] Recent rapid spread of the Internet brings a plurality of service providing sites providing a variety of different services, such as information provision, commodity sales, or mail delivery. A user who wants to use these services can ~~access to~~ the above described service providing sites and gets these services with relatively easier procedures by using a personal computer connected to the Internet.

[0003] Some service ~~providenee~~ providing sites become congested because more access requests from the user become centralized at the same time ~~with a reason~~ because of their the sites' higher popularity and the like. ~~Such~~ Accordingly, the more popular sites need to prepare a server having ~~an~~ sufficient ability ~~enough to cope with~~ accommodate the large number of access requests with a high performance.

[0004] In this way, the conventional service providing server via a network is designed ~~so as to be acceptable to~~ accommodate the an estimated number of access requests, ~~with nothing like~~ without accommodating the service providing sites on the Internet.

[0005] When more accesses over the estimated number of accesses become centralized, ~~then, the server does not specially~~ especially deal with the problem, and therefore, a stable service provision cannot be continued ~~such that and~~ the user cannot access ~~to the service with reasons of~~ due to lowering of the server's performance ~~lowering and/or the termination of service providenee~~ caused by the centralized requests. Therefore, some service providing sites need to send messages to cope with users who cannot access the service providing sites.

[0006] However, even when the conventional method is used, the user who cannot access the service ~~repeats sending repeatedly sends~~ the access request to the server ~~over and over~~, because they cannot hold the condition of server; when more accesses over the estimated number become concentrated to one service ~~provision~~providing server, and that causes a vicious circle, such as over load on the server. Further, since the user accessing to the server does not hold the congested condition, the user is not expedited to exit and continues using the service as usual. Therefore, it is impossible to improve the congested condition of the service providing server by ~~finishing completing to use the service an~~ earlier service.

[0007] Moreover, some users give up ~~to~~ access to the site because of the congested condition ~~without such as they cannot understand when they being given any indication as to when the users can access the site~~, and some users have a bad impression ~~to~~of the service ~~providenc~~providing site; because of ~~hardness~~the users' inability to access ~~to~~ the site and/or due to a response delay at the accessed time, ~~so that thus~~ there is a possibility ~~to lose of losing~~ service ~~provision chances~~providing opportunities.

[0008] Therefore, the conventional service ~~provision~~providing method ~~gives the results in~~ larger losses; when more access requests that are over the ability of server become centralized, ~~so that and~~ effective or stable service cannot be provided ~~for more to~~ many ~~persons~~users.

SUMMARY OF THE INVENTION

[0009] Accordingly, it is an object of the present invention to provide a service ~~provision~~providing method and system that provide a stable service via a network by ~~keeping the~~maintaining a stable access condition and ~~suppressing losses~~reducing loss of service ~~providing chances for opportunities to~~ the users ~~to the least~~; when more accesses over the ability of server become centralized.

[0010] In order to attain the above object; according to ~~a first an~~ aspect of the present invention, ~~there is provided a method of includes, informing the~~indicating a number of accesses to a server that provides a service to a user at ~~that a~~ time ~~the an~~ accessible number ~~exceeds is~~ exceeded, when a user sends an access request to ~~a the~~ server, ~~which provides the service~~; with no execution of immediate access to the server, updating the information as ~~occasion~~periodically, and executing the access to the server for the waiting user; when the ~~user server~~ becomes accessible. Therefore, according to the present invention,

~~sincebecause~~ the user concretely holds the user's own waiting state in figures and need not to access ~~the server~~ again ~~tilluntil~~ the user ~~can access to~~ is informed of accessibility of the server, the conventional access repetition and the case where the user gives up to access to the server are decreased. Thereby, when ~~more~~ access requests ~~oversurpass~~ the ability of the server and become centralized, the stable access condition ~~can be held~~ is maintained, ~~lossesloss~~ of the service ~~provision chances~~ providing opportunities can be suppressed, and therefore, effective service provisions can be executed.

[0011] Further, ~~in~~ according to the preferred mode of the above invention, when ~~the~~ access to the server becomes available, ~~it is informed for the user~~ is informed that the server is to be accessible by a display screen, voice or E-mail before executing the connection.

[0012] Additionally, ~~in the other~~ according to another mode of the ~~above~~ invention, a period of updating the information of the number of accesses is varied according to ~~the~~ information of related to the number of accesses.

[0013] According to ~~the more~~ another preferred mode of the ~~above~~ invention, an estimated time ~~tilluntil~~ the ~~user~~ server becomes ~~accessable~~ accessible, which is obtained according to ~~the~~ a time variation of the information of the number of accesses, is ~~informed~~ indicated to the user with the information of the number of accesses.

[0014] Furthermore, ~~in the other~~ according to yet another mode of the ~~above~~ invention, when a commodity sale service is provided, ~~the~~ a number of goods in stock is ~~informed~~ indicated to the user with the information of access number.

[0015] Moreover, ~~in the other mode of the above invention~~, when the access requests to the server, which provides the service, become more than the ~~accessable~~ accessible number, information of the number of accesses is ~~informed for~~ indicated to all users who are using the server.

[0016] ~~The above and other objects, aspects, features and advantages of the present invention will become more apparent from the following detailed description of a preferred embodiment thereof.~~

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] The above and other objects, aspects, features and advantages of the present invention will become more apparent from the following detailed description of a preferred embodiment thereof.

FIG. 1 is a structural diagram of a service provision system applied to the present invention;

FIG. 2 is a diagram showing a processing flow chart, when an access request is sent to the service provision system according to the present embodiment;

FIG. 3 is a diagram showing one example of a display screen showing information of the number of accesses;

FIG. 4 is a diagram showing one example of a display screen displayed for users, when access to the site becomes available;

FIG. 5 is a diagram showing one example of an electric mail sending the user when access to the site becomes available;

FIG. 6 is a diagram showing one example of display screen showing information of the number of accesses when displaying an estimated time (~~estimated accessible~~ accessible time) till they can access to the site.

FIG. 7A shows one example of a display screen of urging users to input password and FIG. 7B shows one example of display screen after password authorization;

FIG. 8 is a diagram showing one example of display screen for displaying the number of goods in stock for users;

FIG. 9 is a diagram showing one example of display screen for informing no goods in stock for user;

FIG. 10 is a diagram showing one example of E mail for informing no goods in stock for users; and.

FIG. 11 is a diagram showing one example of urging screen displayed for the accessing user.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0018] Presently preferred embodiments of the present invention will now be described with reference to the accompanying drawings. However, such embodiments do not limit the technical

scope of the present invention. The same reference numerals are used to denote and identify corresponding or identical components.

[0019] FIG. 1 is a structural diagram of a service ~~provision~~providing system applied to the present invention. The service ~~provision~~providing system according to the present embodiment includes a server of a service provider side, which ~~is composed of~~comprises a server 1 for allocating accesses addressed to the server, ~~and~~ a server 2 for queuing for connection and a contents server 3, ~~and~~. Further, a section 51 for indicating information of the number of accesses and a section 52 for regularly obtaining the number of accesses in a client 5, which is a terminal machine owned by a user who gets the service provision, are provided to the service providing system.

[0020] The client 5 is a client system ~~composed of~~including a personal computer, which is ~~accessible~~accessible to the above-described server via a network, such as the Internet. Additionally, software for getting a service from the server, such as a browser for the Internet, is provided. The user of the service provision system uses the software to access the server to get the service ~~provision~~provided. In this example, a plurality of clients 5 may exist on the network 4.

[0021] The destination allocating server 1, which ~~is composed of~~includes a computer system, such as a personal computer or a ~~work station~~workstation, takes a part of allocating the destinations of client 5 into the connection queuing server 2 or the contents server 3; when the user ~~sends~~sends an access request through the above described client 5.

[0022] As is shown in FIG. 1, the destination allocating server 1 includes a destination allocating processing section 11 for allocating the destination and an accessed number informing section 12 for informing the number of accesses. The destination allocating processing section 11 having a unique address on the network 4 (In the case of the Internet, the unique address means URL) is connected first ~~to~~with the unique address when the user sends the access request, where the above described allocation is executed. Every time the user sends the access request, the destination allocating processing section 11, which manages an access number, issues a unique access number for the access request. In this example, the access number ~~means the~~includes a total number of access requests for ~~this~~the particular

service provision system, of which initial value is zero and ~~to which one~~ increases every time an access request ~~incomes~~ is received.

[0023] Further, the accessed number informing section 12 takes a part of sending and receiving information associated ~~to~~ with the access number to the service ~~provision~~ providing system, such as the above described accessed number, to and from the connection queuing server 2. Moreover, it is desirable to ~~mount~~ implement the destination allocating processing section 11 and the accessed number informing section 12 ~~by~~ using a computer program and a control device for executing ~~processes~~ operations according to the computer program.

[0024] Next, the connection queuing server 2 including ~~a~~ an accessed number management section 21 and an accessed number informing section 22, as shown in FIG. 1, is a server, ~~to~~ with which the client 5 are connected; when the user cannot access ~~to~~ the contents server 3 for executing actual service provision ~~in~~ at the time of sending the access request from the client 5, i.e., more access requests over the ability of contents server 3 ~~become~~ are centralized.

[0025] The accessed number management section 21 having a unique address on the network 4 provides information associated ~~to~~ with the number of accesses to this service provision system. The section 21 further manages a submitted ~~accessible~~ accessible number ~~meaning~~ indicating the above described access number ~~showing the~~ including an upper limitation enabled to access ~~to~~ the contents server 3. As a value of submitted ~~accessible~~ accessible number, a value of ~~the~~ a maximum connectable number of accesses to the contents server 3 (~~correctly speaking~~ specifically, it ~~is~~ to a contents service section 31 described later) is used at the initial state, and ~~one increases to the value,~~ is incremented every time the connection ~~to~~ with the accessing client 5 is ~~finished~~ completed.

[0026] When the maximum connectable number is 1000, the initial value of the submitted ~~accessible~~ accessible number is '1000', and the value increases ~~one by one every~~ each time the connection with the accessing clients 5 is ~~finished~~ completed, ~~as for example,~~ for example, 1001, 1002...etc.

[0027] Additionally, the accessed number informing section 22 sends and receives information associated ~~to~~ with the number of accesses between the destination allocating server 1 and the contents server 3 and updates the above-described submitted ~~accessible~~ accessible number according to the information ~~of~~ in relation to access termination, which is transmitted from the contents server 3, and similarly to the accessed number informing section 12. Further,

it is desirable ~~to compose that~~ the connection queuing server 2 ~~of~~includes a computer system, such as a personal computer or a ~~work station~~workstation, and ~~to mount~~is implemented with the accessed number management section 21 and the accessed number informing section 22 ~~by using~~ a computer program and a control device for executing the ~~process~~operation according to the program.

[0028] The contents server 3, ~~which includes~~including a contents service section 31 and the accessed number informing section 32, ~~actually~~ provides a service in the service provision system. The contents service section 31 having a unique address on the network 4 provides a variety of prepared services ~~for~~to the client 5 who ~~permits~~is permitted to access this address. ~~More specifically~~For example, the contents server 3 provides information and sells goods according to an operation on the client 5 owned by the user. The accessed number informing section 32 sends and receives information associated ~~to~~with the number of accesses to and from the connection queuing server 2.

[0029] It is also preferable ~~to compose that~~ the contents server 3 ~~of~~includes a computer system, such as a personal computer or ~~work station~~workstation, similar to the other servers, and ~~to mount~~implement the contents service section 31 and the accessed number informing section 32 ~~by using~~ a computer program and the control device executing the ~~processes~~operations according to the program.

[0030] Subsequently, the accessed number information displaying section 51 and the accessed number regularly obtaining section 52 ~~activate~~are activated, when one client 5 who sends one access request is connected ~~to~~with the above described connection queuing server 2, i.e., the client 5 waits for the connection ~~to~~with the above described contents service section 31, regularly ~~obtain~~obtains information relating to the number of accesses from the connection queuing server 2, and informs the queuing condition to the user by displaying the information on the client 5. ~~In here~~According to an aspect of the invention, it is preferable that the accessed number information displaying section 51 and the accessed number regularly obtaining section 52 are ~~respectively composed of~~implemented using Java applet transmitted from the connection queuing server 2 to the client 5; when the client 5 is connected ~~to~~with the connection queuing server 2.

[0031] Although the destination allocating server 1, the connection queuing server 2 and the contents server 3, are individually composed of three servers, each of which is independent, it ~~may be applied to compose these~~ is possible to implement operations of the three servers ~~by using~~ one server to logically share a resource and manage the shared resource.

[0032] As is described above, in the service provision system relating to the present invention, when more access requests over that of the ability of the service ~~providing~~ providing server become concentrated, ~~the a~~ queuing condition is informed periodically provided to the user until the user can access ~~as occasion~~ the service providing server, without immediately ~~accessing~~ allowing the user to access the server, and the user can access to the server; when the user becomes ~~accessible~~ accessible.

[0033] FIG. 2 shows a flowchart describing when an access request to the service provision system according to the present invention occurs. At first, a user who employs the service provision system requests access to the service provision system from a browser of a client 5 (StepOperation S1 of FIG. 2). Then, the client 5 is connected ~~to~~ with the destination allocating processing section 11 of the destination allocating server 1, and then, the destination allocating processing section 11 counts ~~up one to~~ the above described access number and issues one access number for one access request (StepOperation S2 of FIG. 2).

[0034] Next, the destination allocating processing section 11 queries the submitted ~~accessible~~ accessible number at that time to the accessed number management section 21 in the connection queuing server 2 through the accessed number informing section 12 and 22 (StepOperation S3 of FIG. 2), and the management section 21 transmits the submitted ~~accessible~~ accessible number to the destination allocating processing section 11 in response to the query (StepOperation S4 of FIG. 2). The destination allocating processing section 11 compares the received submitted ~~accessible~~ accessible number with the above issued access number and connects the client 5 ~~to~~ with the contents service section 31 of the contents server 3; immediately (StepOperation S6 of FIG. 2); when the access number is less than the submitted ~~accessible~~ accessible number (Yes of the stepoperation S5 of FIG. 2).

[0035] As the result of the comparison, when the access number is larger than the submitted ~~accessible~~ accessible number (No of the stepoperation S5 of FIG. 2), the destination allocating processing section 11 connects the client 5 ~~to~~ with the management section 21 of the

connection queuing server 2 (StepOperation S7 of FIG. 2);~~and~~ the client 5 becomes in the queuing state. In response to that, the management section 21 transmits the information of the number of accesses, i.e., the access number of the client 5 and the submitted ~~aeessable~~accessible number at that time, with a program, which composes the above described accessed number information indicating section 51 and the accessed number regularly obtaining section 52 (StepOperation S8 of FIG. 2).

[0036] The transmitted information of the number of accesses is displayed ~~fer~~to the user by the accessed number information indicating section 51 on the client 5 receiving the above-described transmission (StepOperation S9 of FIG. 2). FIG. 3 is a diagram showing ~~one an~~ example of the display screen. In the diagram, an x section represents the submitted ~~aeessable~~accessible number and a y section represents an access number of the client 5. The user can hold the state of queuing for connection ~~at the indication of~~as indicated by the display screen. It ~~may be applied~~is possible to display how many persons there are before connecting a certain client ~~to~~with the server, i.e., a value obtained by subtracting the value of x section from the value of y section shown in FIG. 3, without displaying submitted ~~aeessable~~accessible number and the access number, as shown in FIG. 3.

[0037] In this way, the accessed number regularly obtaining section 52 of the queuing client 5 queries the submitted ~~aeessable~~accessible number according to the above described transmitted program ~~in aat~~ predetermined constant time interval at the queuing client 5 (StepOperation S10 of FIG. 2). Additionally, it ~~may be applied~~is possible to automatically adjust ~~thea~~ time interval for this query ~~in consideration of~~based on the load on the connection queuing server 2 without fixing ~~thea~~ time interval of this query. More specifically, the time interval for query is varied according to the number of the clients 5 for querying to the management section 21 in the access queuing state, for example, the value obtained by subtracting the value of x section from the value of y section shown in FIG. 3. Assuming that the connection queuing server 2 has a processing ability that is enough to reply to 1000 access requests at the ~~sameone~~ time and requires 2 seconds for every query process, the time interval for query is set to two seconds when ~~thea~~ number of the access queuing clients is 1000, and ~~thea~~ time interval for query is set to ten seconds ($2 \times (5000/1000)=10$), when the number of access queuing clients becomes 5000. Thereby, the time interval for query ~~can be~~is set to be longer, even when the number of clients 5 is larger, and the load on the connection queuing server 2 ~~can be~~is lighter~~is reduced~~, so that a constant response performance ~~can be held~~is maintained.

[0038] The management section 21, which receives the query, transmits the submitted ~~aeessable~~accessible number at that time to the client 5 (StepOperation S11 of FIG. 2), the accessed number regularly obtaining section 52 compares the submitted ~~aeessable~~accessible number with the access number of the client 5 (StepOperation S12 of FIG. 2). As the result of the comparison, when the access number is larger than the submitted ~~aeessable~~accessible number (No of the stepoperation S12 of FIG. 2), i.e., the access is not permitted, the ~~processes~~operations from the stepoperation S9 of FIG. 2 are repeated and are executed. On the other hand, when the access number is less than the submitted ~~aeessable~~accessible number (Yes of the stepoperation S12 of FIG. 2), the accessed number regularly obtaining section 52 connects the client 5 ~~to~~with the contents service section 31 of the contents server 3 (StepOperation S13 of FIG. 2).

[0039] In this embodiment, it may be executed to connect ~~to~~with the contents service section 31 automatically at the time of accepting the condition or it may be applied to display the connectable information on the client 5 to get the confirmation operated by the user. FIG. 4 is a diagram showing ~~one an~~ an example of a display screen ~~indicated for~~displayed to the user before executing the access request. If the user wants to access ~~to~~ the site, the user ~~can~~ aeessaccesses to the contents service section 31 by selecting a section shown as an "entrance".

[0040] ~~It may be applied to inform~~According to an aspect of the invention, the user ~~to become~~is informed of accessibility of the server ~~aeessable~~ by E-mail as shown in the example of FIG. 5. In this case, the user ~~need~~needs to pre-register the mail address in this service provision system, and ~~to input data for identifying~~ to specify the mail address at some stages of the access queuing time. ~~It may be~~is also applied possible to inform the user ~~to become~~ ~~aeessable~~of the server's accessibility by voice. Alternatively, it may be applied that the user can select the informing methods using by a display screen, E-mail or voice.

[0041] In the present embodiment, although the ~~steps~~operations S9, S10, S12 and S13 of FIG. 2 are executed at the client 5 according to a program like Java applet transmitted to the client 5, it may be applied to execute these ~~processes~~operations at the connection queuing server 2. In this case, when information of the number of accesses is displayed to the client 5, it can be applied to transmit a HTML file of the display screen displaying the information of the number of accesses from the connection queuing server 2.

[0042] Returning back to FIG. 2, if the client 5 can access to the contents server 3 (~~Steps~~Operations S6 and S13 of FIG. 2), the user can get the service providence prepared at the contents service section 31 (Step S14 of FIG. 2). After that, when the user finishes (logs out) accessing to the contents server 3 or the contents server 3 forces finishing (sessions out) to access to the user with a reason because of no access from the user ~~and the like, etc.~~ the contents service section 31 informs ~~that~~the same to the management section 21 through the accessed number informing sections 32 and 22 (~~Step~~Operation S15 of FIG. 2). The management section 21, which receives the information, counts ~~one up to~~ the submitted ~~aeccessable~~accessible number according to the access termination information (~~Step~~Operation S16 of FIG. 2).

[0043] Although ~~processes~~operations from the time of sending an access request to the service provision system to the time of finishing the connection are explained above, the overflowed access requests are connected ~~to~~with the connection queuing server; not to the service provision server; when more access requests over the ability of server, which provides services, become centralized in this service provision system. Even if more access requests become centralized, therefore, a stable service provision ~~can be~~is executed without lowering the response performance of the server, which provides a service. Additionally, the queuing state is concretely shown to the queuing user in figures, and therefore, the conventional access request repeating operation ~~can be~~is prevented. Moreover, since the user can estimate the waiting time before the user can access, ~~it becomes decreased~~the possibility that the user thoughtlessly gives up to get the service is decreased ~~or~~and the user ~~can wait~~waits easily by effectively using the waiting time for executing some other operations ~~til~~until the user can access to the service.

[0044] As the modified example according to the above-described embodiment, it may be applied to display the estimated time (estimated ~~aeccessable~~accessible time) for the queuing user with the information of the number of accesses. FIG. 6 shows ~~one~~an example of the display screen at that time. The bottom section of the display shows the above described estimated time. In this example, the user ~~can know~~is notified that it takes about twenty minutes to access the service. Moreover, the estimated time (estimated ~~aeccessable~~accessible time) ~~can be~~is obtained according to the condition of counting or increasing the submitted ~~aeccessable~~accessible number as ~~the following procedures:~~described below.

[0045] The accessed number management section 21 of the connection queuing server 2 that manages the submitted ~~accessable~~accessible number holds the condition of counting the number ~~in~~according to a predetermined timing and transmits information of the condition of counting the number in addition to the accessed number information every time queuing is received from the accessed number regularly obtaining section 52. The accessed number regularly obtaining section 52 of the client 5, which receives the transmission, calculates the above-described estimated time (estimated ~~accessable~~accessible time) from the information of the number of accesses and the information showing the condition, and displays the value to the user on the accessed number information displaying section 51.

[0046] When the submitted ~~accessable~~accessible number is counted up to 1000 for ~~past~~ five minutes, for example, the submitted ~~accessable~~accessible number is 10000 and the access number is 30000, the estimated time (estimated ~~accessable~~accessible time) ~~can be~~is obtained by calculating $(30000-10000)=1000 \times 5 \text{ minutes}=100 \text{ minutes}$. In this way, the users ~~can~~hold/maintain the queuing condition; accurately, ~~by displaying~~the user is informed of the estimated time in addition to the information of the number of accesses, and therefore, ~~it makes possible to obtain more effectiveness~~allows effective service to be provided to the user. Moreover, it also becomes possible to obtain the estimated time (estimated ~~accessable~~accessible time) at the connection queuing server 2 and transmit the result to the client 5.

[0047] FIG. 7A and FIG. 7B are diagrams for explaining ~~the other modified example~~other examples of the invention. The ~~modified example~~modified example shows a ~~method of~~display screen of ~~urging/prompting~~urging/prompting the user to input a password and ~~accessing~~allowing access of the client 5, ~~of which~~which the user uses, immediately to the contents server 3 regardless of the number of access requests at that time; ~~if/when~~when the inputted password is correct. The user's password input maybe executed at the first access request or the password input may be executed on a display screen of the information of the number of accesses displayed ~~for~~to the user; while the user is queuing.

[0048] FIG. 7A shows ~~one~~an example of the input display screen of the latter case. If the user inputs a password on the display screen and the input password coincides with one of passwords pre-registered at the connection queuing server 2, the ~~user~~contents server 3 becomes ~~accessable~~accessible to the ~~contents server 3~~user, and the display screen as shown

in FIG. 7B is displayed on the client 5. In this example, the user ~~can connect to~~connects with the contents server 3 to get the service ~~provision~~provided by selecting a section shown as "Entrance". Additionally, in the modified example, a password authentication section for authentication of the above-described password and a password record section for registering the password are provided at the connection queuing server 2. The addition of the password inputting function makes it possible to execute rapid service provision for specified user ~~as at a~~at a certain occasion.

[0049] Moreover, ~~as the other modified example,~~ when the service provision is targeted for commodity sales, ~~it may be applied to a display of~~ the number of goods in stock with the information of the number of accesses is provided. This is a case where a service called a shopping ~~mail~~email is provided, and FIG. 8 shows ~~one an~~an example of the display screen displayed for the user. In this case, the management section 21 of the connection queuing server 2 obtains the information every time the goods ~~is are~~are sold from the contents server 3, obtains the number of goods in stock, and transmits the number of goods in stock with the information of the number of accesses; when querying from the accessed number regularly obtaining section 52 to the client 5. Moreover, the number of goods in stock may be obtained at the contents server 3 ~~in at selling time of every goods-selling time~~good.

[0050] Additionally, ~~in the modified example,~~ when the number of goods in stock becomes zero, not only zero is displayed on the above described display screen, but a special display screen that shows no stock is displayed ~~for to~~to the clients, for example, a message ~~informing to~~indicating no stock. FIG. 9 is a diagram showing ~~one an~~an example of the display screen. Furthermore, ~~one a~~a method for transmitting ~~E-mail~~email as shown in ~~one the~~the example of FIG. 10 to the registered address of the user and ~~the other a~~a method for transmitting the information of no stock from the client 5 to the user by voice are used instead of the display screen showing no stock. In this way, in the service provision system, which provides a commodity sale service, not only ~~losses of user's chances caused by giving up to buy goods can be~~loss of providing services to the user is decreased but the load on the server caused by the user's access ~~regardless of no goods can be lightened~~whether there are goods is reduced.

[0051] Moreover, ~~in the other modified example,~~ when more access requests over the ability of the service providing system become concentrated and the queuing clients 5 exist, ~~it may be applied that~~ a display screen for ~~urging~~prompting the users who are accessing ~~to~~ the contents

server 3 to ~~get~~complete the service to ~~finish~~of the previous access ~~earlier~~is provided. FIG. 11 is a diagram showing ~~one~~an example of the display screen. In this modified example, when the accessed number becomes larger than the submitted ~~accessable~~accessible number, the management section 21 of the connection queuing server 2 transmits the information to the contents service section 31 of the contents server 3, the contents service section 31 receives the information and transmits the above described urging screen to the accessing clients 5. The urging display screen ~~urges~~prompts the user to use the service earlier, because of user's apprehension for response speed delay or out of stock in the commodity sale service. As the result, the user finishes to access the contents server 3 earlier than usual so that the access condition can be improved, when access requests become concentrated.

[0052] Hereinabove, according to a service provision system of the present invention, it becomes possible to keep stable access condition of the server providing the service, even when access requests become concentrated, and to ~~suppress~~reduce losses of service ~~provision chances for user to the least~~providing opportunities. Therefore, it ~~also becomes~~is possible to execute effective and stable service provision ~~for~~to users.

[0053] It should of course be understood that those, which are the same as the technical concept of the invention, are within the protective scope of the invention.

[0054] According to the present invention, even when users cannot access ~~to~~ a desired server immediately, ~~they can hold their own condition in figure~~the users maintain respective conditions and have no need to access the server again till they becomeuntil the server becomes ~~accessable~~accessible, and therefore, the conventional access repetition is decreased and the user's unreasonable giving up ~~to~~of access is also decreased. Therefore, even if access requests over the ability ~~occur~~of the server occurs, it ~~becomes~~is possible to keep stable access condition and ~~suppress~~decrease the losses of service ~~provision chances~~providing opportunities, and therefore, effective service provision ~~can be~~is executed.

[0055] Although the invention has been described with respect to a specific embodiment for a complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying all modifications and alternative constructions that may occur to one skilled in the art which fairly fall within the basic teaching herein set forth.

ABSTRACT OF DISCLOSURE

A service ~~provision~~providing method and system; ~~by~~according to which a stable access condition ~~can be held to the utmost~~is maintained, losses of service providing ~~chances~~for opportunities to users ~~are reduced~~can be suppressed to the least and a stable service can ~~be~~is provided via a network are provided. When an access request is sent from a user to a service providing server and ~~the an~~an ~~accessable~~accessible number ~~exceeds~~is exceeded, the server ~~informs~~indicates information of the number of accesses ~~at that time~~to the user without immediately executing the access to said server, updates the information ~~as~~periodically and connects the user ~~to~~with the server when the server becomes ~~accessable~~accessible.